

Plastic Flexible Conduit (Corrugated Conduit)



◆ **Materials and Temperature:**

- (1) PA: -40℃~+130℃ Fire-proof: V0(UL94)
- (2) PP: -30℃~+110℃ Fire-proof: V0(UL94)
- (3) PE: -30℃~+100℃

◆ **Properties:**

Flexible, Smooth Surface, Acid-Alkaline Resistant, Friction Resistant, Durable etc.

◆ **Using Place:**

Machinery, Construction, Shipping, Automation, Auto and other wire/cable protection industry.

◆ **Certificates:**

ISO9001:2008, Rohs, TS 16949:2009

PA	PP	PE	ID*OD(mm)	Packing Unit(m)
Flex-PA-7B	Flex-PP-7B	Flex-PE-7B	4.5*7.0	200
Flex-PA-8.5B	Flex-PP-8.5B	Flex-PE-8.5B	5.5*8.5	100
Flex-PA-10B	Flex-PP-10B	Flex-PE-10B	6.5*10.0	100
Flex-PA-11.5B	Flex-PP-11.5B	Flex-PE-11.5B	8.5*11.5	100
Flex-PA-13.0B	Flex-PP-13.0B	Flex-PE-13.0B	10.0*13.0	100
Flex-PA-15.8B	Flex-PP-15.8B	Flex-PE-15.8B	12.0*15.8	100
Flex-PA-18.5B	Flex-PP-18.5B	Flex-PE-18.5B	14.3*18.5	100
Flex-PA-21.2B	Flex-PP-21.2B	Flex-PE-21.2B	17.0*21.2	100
Flex-PA-25.0B	Flex-PP-25.0B	Flex-PE-25.0B	21.0*25.0	100
Flex-PA-28.5B	Flex-PP-28.5B	Flex-PE-28.5B	23.0*28.5	50
Flex-PA-34.5B	Flex-PP-34.5B	Flex-PE-34.5B	29.0*34.5	50
Flex-PA-42.5B	Flex-PP-42.5B	Flex-PE-42.5B	36.0*42.5	25
Flex-PA-54.5B	Flex-PP-54.5B	Flex-PE-54.5B	48.0*54.5	25
Flex-PA-67.2B	Flex-PP-67.2B	Flex-PE-67.2B	56.3*67.2	25
Flex-PA-80.0B	Flex-PP-80.0B	Flex-PE-80.0B	66.5*80.0	20
Flex-PA-106B	Flex-PP-106B	Flex-PE-106B	91.0*106.0	20

General color is Black, blacks' all sizes are in stock. Colors, sizes, packages etc customizable are workable.