

**Split Loom Tubing**



◆ **Materials and Temperature:**

- (1) PA: -40°C~+130°C      Fire-proof: V0(UL94)
- (2) PP: -30°C~+110°C      Fire-proof: V0(UL94)
- (3) PE: -30°C~+100°C

◆ **Properties:**

Flexible, Smooth Surface, Acid-Alkaline Resistant, Friction Resistant, Durable etc.

◆ **Using Place:**

Machinery, Construction, Shipping, Automation, Auto and other wire/cable protection industry.

◆ **Certificates:**

ISO9001:2008, Rohs, TS 16949:2009

PA	PP	PE	ID*OD(mm)	Packing Unit(m)
Flex-PA-7K	Flex-PP-7K	Flex-PE-7K	4.5*7.0	200
Flex-PA-8.5K	Flex-PP-8.5K	Flex-PE-8.5K	5.5*8.5	100
Flex-PA-10K	Flex-PP-10K	Flex-PE-10K	6.5*10.0	100
Flex-PA-11.5K	Flex-PP-11.5K	Flex-PE-11.5K	8.5*11.5	100
Flex-PA-13.0K	Flex-PP-13.0K	Flex-PE-13.0K	10.0*13.0	100
Flex-PA-15.8K	Flex-PP-15.8K	Flex-PE-15.8K	12.0*15.8	100
Flex-PA-18.5K	Flex-PP-18.5K	Flex-PE-18.5K	14.3*18.5	100
Flex-PA-21.2K	Flex-PP-21.2K	Flex-PE-21.2K	17.0*21.2	100
Flex-PA-25.0K	Flex-PP-25.0K	Flex-PE-25.0K	21.0*25.0	100
Flex-PA-28.5K	Flex-PP-28.5K	Flex-PE-28.5K	23.0*28.5	50
Flex-PA-34.5K	Flex-PP-34.5K	Flex-PE-34.5K	29.0*34.5	50
Flex-PA-42.5K	Flex-PP-42.5K	Flex-PE-42.5K	36.0*42.5	25
Flex-PA-54.5K	Flex-PP-54.5K	Flex-PE-54.5K	48.0*54.5	25

General color is black.

Colors, sizes, fire-proof etc. customizable are workable.